

KRIMPACT FLAT ROOF SLABS

March 2018



APPLICATIONS



DESCRIPTION

Rocksilk Krimpact Flat Roof Slabs are high strength, dense rigid slabs made from Rock Mineral Wool, manufactured using Krimpact technology, specifically designed for use in flat roofing applications.

Products are available in two grades:

- Rocksilk Krimpact Flat Roof Slab
- Rocksilk Krimpact Flat Roof Slab Extra.

Slabs contain a special additive to ensure their water repellency.

PERFORMANCE

Thermal

Thermal conductivity: 0.038 and 0.039W/mK

Fire

Classification: EUROCLASS A1 to BS EN 13501-1

Vapour resistivity

Water vapour resistivity: 5.00MNs/g.m


BENEFITS

- ✓ Non-combustible Euroclass A1 Reaction to Fire rating
- ✓ Improves acoustic performance of flat roof systems
- ✓ High level of compressive strength

SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m ² K/W)	Length (mm)	Width (mm)
Rocksilk Krimpact Flat Roof Slab				
180	0.038	4.70	1200	1000
145	0.038	3.80	1200	1000
120	0.038	3.15	1200	1000
100	0.038	2.60	1200	1000
Rocksilk Krimpact Flat Roof Slab Extra				
150	0.039	3.80	1200	1000
125	0.039	3.20	1200	1000
105	0.039	2.65	1200	1000
95	0.039	2.40	1200	1000

CERTIFICATION



KRIMPACT FLAT ROOF SLABS

March 2018

ADDITIONAL INFORMATION

Durability

Rocksilk Krimpact Flat Roof Slabs are odourless, non-hygroscopic, rot proof, do not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

Application

Rocksilk Krimpact Flat Roof Slabs are used for the thermal insulation of flat roofs. Rocksilk Krimpact Flat Roof Slabs are suitable for use under all kinds of single ply membrane, hot applied bitumen systems and mastic asphalt and are suitable for maintenance foot traffic only.

Standards

Rocksilk Krimpact Flat Roof Slabs are manufactured in accordance with BS EN 13162, ISO 50001 Energy Management Systems, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

Certification

Rocksilk Krimpact Flat Roof Slabs are British Board of Agrément certified (certificate no 08/4526) for use as a thermal insulation layer for limited access at roofs with concrete, timber or metal decks.

Environmental

Rocksilk Krimpact Flat Roof Slabs represent no known threat to the environment and have zero Ozone Depletion Potential and zero Global Warming Potential.

Vapour resistivity

Rocksilk Krimpact Flat Roof Slabs offer negligible resistance to the passage of water vapour and have a water vapour resistivity of 5.00 MN.s.g.m.

Compressive strength

Rocksilk Krimpact Flat Roof Slab has a compressive strength of 60 kPa, Rocksilk Krimpact Flat Roof Slab Extra has a compressive strength of 90 kPa.

Handling and storage

Rocksilk Krimpact Flat Roof Slabs are easy to handle and install, and easily cut to size, where necessary. They are supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Rocksilk Krimpact Flat Roof Slabs should not be left permanently exposed to the elements.

Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens, Merseyside, WA10 3NS. UK

Customer Service: 0844 800 0135

Technical Support Team: 01744 766 666

Literature: 08700 668 660

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE1163DAT-V0318

challenge.
create.
care.